

Features and Benefits

- Incorporates AltroSan™ Integrated bacteriostat
- Incorporates Altro Easyclean™ for ease of cleaning
- Excellent slip resistance
- Low VOC emissions for improved air quality
- Does not contain DEHP or pthalates

Applications

ContraX is ideal for hospitals, elderly care centers, school and cafeterias.

Specifications

ContraX is available in 9 appealing colors.

Product Specification	(All weights and measures are approximate)	
Thickness	0.08"	2.0mm
Roll Length	66'	20m
Width	6'7"	2m
Weight	4.1lbs/yd ²	2.2kg/m ²



Test Results

ASTM Standard	(Tested in accordance with ASTM tests)	
ASTM F 970	Static Load Limit	1000psi
ASTM D 2047	Slip Resistance	D .67
ASTM E 648	Critical Radiant Flux	Pass
ASTM E 662	Smoke Generation	Pass
ASTM F 1303/1700	Physical Properties	Pass
ASTM C 501	Taber Abrasion	Pass
ASTM D 1203	Volatile Loss	Pass
CAN/ULC-S102.2	Surface Burning	Pass

Sustainability

Category	LEED NC&CI Credits	Description Summary
Materials and Resources	4.1 & 4.2	Contains 10% Post Consumer Recycled Content
Indoor Environmental Air Quality	EQ 4.3	Low VOC emitting materials
	EQ 4.1	Low VOC emitting materials

